



F1500 shown with cast iron legs and door with nickel accent.

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & catalytic bypass
- Air & bypass operating tool
- Easy to read catalytic thermometer
- High performance brick-lined firebox
- Clean glass airwash system
- Heavy gauge steel log retainers
- Rear heat deflector
- Mobile home and alcove approved
- Closest clearances in the industry
- 10-year 100% coverage on original catalyst

OPTIONS

- Cast iron door with ceramic glass in black or nickel accent
- Pedestal base
- Cast iron legs in black or brushed nickel
- Ash drawer
- Variable speed blower
- Convector airmate
- Outside air kit

SPECIFICATIONS

Maximum BTU*	55,000
Typical sq. ft. heated**	600 - 1,200
Efficiency (EPA LHV)	84%
Max log size	18"
Burn time	Up to 10 hours
Emissions	1.0 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE



F2500 shown with pedestal base and black cast iron door and airmate.

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & catalytic bypass
- Air & bypass operating tool
- Easy to read catalytic thermometer
- High performance brick-lined firebox
- Clean glass airwash system
- Rear heat deflector
- Mobile home** and alcove approved
- Closest clearances in the industry
- 10-year 100% coverage on original catalyst

**Approved in USA only

OPTIONS

- Cast iron door with ceramic glass in black or nickel accent
- Pedestal base
- Cast iron legs in black or brushed nickel
- Ash drawer
- 2 speed blower
- Convector airmate
- Outside air kit

SPECIFICATIONS

Maximum BTU*	78,000
Typical sq. ft. heated**	1,000 - 2,200
Efficiency (EPA LHV)	81%
Max log size	18"
Burn time	Up to 12 hours
Emissions	1.0 g/h
Firebox size	2.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE



REGENCY PRO-SERIES™ F3500

Large Wood Stove



F3500 shown with pedestal base, contemporary cast iron door and airmate.

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & side mounted catalytic bypass
- Easy to read catalytic thermometer
- High performance brick-lined firebox
- Clean glass airwash system
- Rear heat deflector
- Mobile home and alcove approved
- Contemporary cast iron door with ceramic glass
- 170° opening door for easy loading
- Heavy duty 3/16 in. steel firebox
- Positive cam latching system
- 10-year 100% coverage on original catalyst

OPTIONS

- Ash pan with cover
- 2 speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)

SPECIFICATIONS

Maximum BTU*	75,000
Typical sq. ft. heated**	1,500 - 2,500
Efficiency (EPA LHV)	87%
Max log size	20"
Burn time	Up to 24 hours
Emissions	0.9 g/h
Firebox size	3.0 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE

regency-fire.com



REGENCY PRO-SERIES™ F5200

Extra Large Wood Stove



F5200 shown with pedestal base and black cast iron door and airmate.

FEATURES

- EPA 2020 certified
- Front mounted air adjustment & side mounted catalytic bypass
- Easy to read catalytic thermometer
- High performance brick-lined firebox
- Clean glass airwash system
- Rear heat deflector
- Mobile home and alcove approved
- Contemporary cast iron door with ceramic glass
- 170° opening door for easy loading
- Heavy duty 3/16 in. steel firebox
- Positive cam latching system
- 10-year 100% coverage on original catalyst

OPTIONS

- Ash pan with cover
- 2 speed blower
- Convector airmate
- Outside air kit

SPECIFICATIONS

Maximum BTU*	80,000
Typical sq. ft. heated**	1,500 - 3,000
Efficiency (EPA LHV)	86%
Max log size	22"
Burn time	Up to 30 hours
Emissions	0.9 g/h
Firebox size	4.4 cu. ft.
Flue size	8"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE

regency-fire.com